

Experience a safer  
and more open world

## Rockwood 555 - Lever Extension Flush Bolt



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626

### SIZE:

Face Plate: 1" x 6 <sup>3</sup>/<sub>4</sub>"

Strike: <sup>15</sup>/<sub>16</sub>" x 2 <sup>1</sup>/<sub>4</sub>"

Guide: 1" x 2"

### WEIGHT:

1.5 lbs./2

ANSI A156.16:

L04251

### Specifications:

#### MATERIAL:

Brass

#### FASTENERS:

8 ea. #8 x <sup>3</sup>/<sub>4</sub>" Flat Head Combo Screws

#### FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- Fits ANSI A115 door and frame preparation
- <sup>3</sup>/<sub>4</sub>" bolt throw, <sup>3</sup>/<sub>4</sub>" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 <sup>1</sup>/<sub>2</sub>" adjustable bolt head

#### OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Extra long bolt head - 2 <sup>1</sup>/<sub>2</sub>" (or to your specification)
- Use #570 Dust Proof Strike to prevent dirt blocking bottom strike



### WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).